

Real distance [cm]	Bluetooth Chanel Sounding				Ultra WideBand (TWR)			
	min value [cm]	average value [cm]	max value [cm]	error of average value	min value [cm]	average value [cm]	max value [cm]	error of average value
50	45	60	75	20,00%	43	49	54	-3,00%
100	91	97	102	-3,50%	93	96	99	-4,00%
150	141	145	148	-3,70%	143	146	148	-3,00%
200	241	251	260	25,30%	192	194	196	-3,00%
250	240	249	258	-0,40%	249	252	255	0,80%
300	320	328	336	9,30%	289	292	295	-2,70%
350	403	408	412	16,40%	342	345	347	-1,60%
400	420	432	443	7,90%	399	401	403	0,30%
450	536	543	550	20,70%	447	450	453	0,00%
500	691	709	727	41,80%	499	501	503	0,20%
600	766	785	803	30,80%	605	608	610	1,30%
700	693	712	731	1,70%	700	701	701	0,10%
800	790	808	826	1,00%	801	808	814	0,90%
900	849	856	863	-4,90%	908	909	910	1,00%
1000	1154	1164	1173	16,40%	1020	1028	1035	2,80%
1500	1659	1668	1677	11,20%	1510	1524	1537	1,60%
1900	2052	2068	2084	8,80%	1878	1884	1890	-0,80%
2400	2557	2578	2599	7,40%	2390	2403	2415	0,10%
3500	3603	3652	3701	4,30%	3465	3479	3492	-0,60%
4400	4582	4637	4692	5,40%	4412	4422	4431	0,50%
5000	4812	4944	5076	-1,10%	4998	5011	5023	0,20%